Name :	
Roll No. :	(Temperature)
Invigilator's Signature :	View /

CS/M.Tech (CSE)/SEM-1/CSTE-21/2010-11 2010-11 MOBILE COMMUNICATION – I

Time Allotted : 3 Hours

Full Marks : 70

The figures in the margin indicate full marks. Candidates are required to give their answers in their own words as far as practicable.

Answer Question No. 1 and any *two* from the rest.

- a) "Due to complexity of the environment it is impossible to derive theoretically a model which predicts the net resulting wave in radio propagation as a function of distance in real environment." Do you agree with this statement ? If yes, suggest a suitable method to deal with the above problem.
 - b) Discuss how synchronization is achieved in a GSM network ? State the reasons for delays in a GSM system for packet data traffic.
 - c) Suggest a technique to improve network coverage and capacity in cellular systems.

40080

[Turn over

CS/M.Tech (CSE)/SEM-1/CSTE-21/2010-11



- d) In a TDMA cellular system, the one way bandwidth is 12.5 MHz. The channel bandwidth is 30 kHz and there are 395 voice channels in the system. The frame duration is 40 ms, with 6 time slots per frame. The system has an individual user data rate of 16.2 kbps in which the speech with error protection has a rate of 13 kbps. Calculate the efficiency of the TDMA frame. 5
- 2. a) Explain the "free space propagation model" to predict the strength of the received signal at a distance from the transmitter.
 - b) A mobile device can at best find six mobile devices reaching in its vicinity. Let there be FDMA mode access by a node. Assuming that f_{w0} is the bandwidth requirement between two neighbours, what bandwidth will be needed when all next hop neighbours communicate in full duplex mode and in same time slots ? If each node path and each direction hop is scheduled to operate at different instants, as in TDMA, then what will be the required bandwidth ? 5
 - c) Estimate the number of mobile users that can be supported by a CDMA system using a RF bandwidth of 1.25 MHz to transmit data at 9.6 kbps. Assume $E_b/N_0 = 6$ dB, frequency reuse efficiency is 0.45, bandwidth efficiency factor is 0.9 and efficiency of sector-antenna in cell is 1. Suppose the voice activity factor for the talk spurts is 60% and the power control accuracy is 80%. What is the number of mobile users that now can be supported ?

40080

CS/M.Tech (CSE)/SEM-1/CSTE-21/2010-11

- d) Discuss why the relative motion between the base station and the mobile results in random frequency modulation.
- a) How is synchronization achieved in a GSM network ?
 What are the reasons for delays in a GSM system for packet data traffic ?
 - b) Discuss the factors influencing small-scale fading. 5
 - c) What is the significance of Delay spread of a multipath channel ?5
 - d) The PDC TDMA system uses a 42 kbps data rate to support 3 users per frame. Each user occupies two of the six time slots per frame.
 - i) What is the raw data rate provided for each user ?
 - ii) If the frame efficiency is 80% and the frame duration is 6.667 ms, determine the number of information bits sent to each user per frame.
 - iii) If half-rate speech coding is used, six users per frame are accommodated. Determine the number of information bits provided for each user per frame.
 - iv) What is the information data rate in half-rate PDC ? 10

3

40080

[Turn over

CS/M.Tech (CSE)/SEM-1/CSTE-21/2010-11



4. a) Prove that for a hexagonal geometry, the co-channel reuse ratio is given by $Q = \sqrt{3N}$ where $N = i^2 + ij + j^2$. 8

- b) We consider a cellular system in which total available voice channels to handle the traffic are 960. The area of each cell is 6 km^2 and the total coverage area of the system is 2000 km². Calculate
 - i) the system capacity if the cluster size, N (reuse factor), is 4 and
 - ii) the system capacity if the cluster size is 7. How many times would a cluster of size 4 have to be replicated to cover the entire cellular area ? Does decreasing the reuse factor *N* increases the system capacity ? Explain.
- c) Usually picocells and microcells are made of splitting the macrocells. Develop a theory for designing macrocells by grouping the microcells and picocells. 5
- d) Discuss how radio propagation characteristics determine the carrier-to-interference ratio at a given location.

40080